

FORGED CHROME PLATED FIRE HOSE LANDING VALVE "PRESSURE RESTRICTING"

Features

Forged chrome plated construction eliminates pinholes and leaks compared with lower quality cast brass construction. Available with female threaded outlet as standard, threaded inlet, BS336 Adaptor outlet.

Working pressure
300 PSI | 20 Bar

Optional finishes

Forged finish | Polished | Forged chrome plated
Forged polished chrome plated

Made : India / China
Brand : OMEX / Blue Seal / Tahadi
: JY : J281 / Newage - NI101



Double Female- Angle
Height from Floor: 0.9-1.2mr

Material Specification

Part name	Material	ASTM Specification
Body	Forged brass	ASTM B 16
Bonnet	Forged brass	ASTM B 16
Nut	Forged brass	ASTM B 16
Hand wheel	Cast Iron	ASTM A48 class 35
Stem	High Tensile Brass	ASTM B 16
Seat	PTFE	Commercial
Washer	High Tensile Brass	ASTM B 16
O-rings	PTFM	Commercial

Dimensions (mm)

Size	1-1/2" / 40	2-1/2" / 65
L	2.17/ 55	3.15/ 80
H (open)	7.70/ 195.5	10.69 / 272
H (closed)	6.61 / 168	8.9/ 226

- * Built in pressure restriction valve
- * If full pressure is required the restriction may be overridden